



1 Multi layer joints of the stainless steel micropump

2 Packaged stainless steel micropump μ P304

STAINLESS STEEL MICROPUMPS FOR MEDICAL-, LABORATORY- AND ANALYSIS TECHNOLOGY

Fraunhofer Research Institution for Microsystems and Solid State Technologies EMFT

Hansastraße 27 d
80686 München
Phone: +49 89 54 75 90
Fax: +49 89 54 75 95 50
E-Mail: contact@emft.fraunhofer.de

Project manager:
Christian Wald
Christian.Wald@emft.fraunhofer.de

www.emft.fraunhofer.de

Applications

In the field of laboratory and medical technology, the dosage of minimal quantities of fluids or gases is crucial. This requires efficient and reliable, yet economic micro-dosage systems. The piezoelectrically driven stainless steel microdiaphragm pumps, developed at Fraunhofer EMFT, generate flow rates of up to 200 ml/min (air) and up to 80 ml/min (water). They are suitable for various applications, such as:

- Negative pressure wound therapy (for the treatment of chronic wounds)
- Medical implants (e.g. drug delivery, artificial sphincter implant)
- Infusion pumps
- Air sampling for gas sensors
- Autonomous cell culture devices

Advantages

- Small size and scalable flow rates allow a wide range of applications
- Accurate dosing due to stroke volumes in microliter range
- Patent-registered piezo assembly process ensures a high back pressure capability with air as well as selfpriming and bubble tolerance with water
- Spring steel material provides excellent long-term properties
- All components in contact with the medium are biocompatible
- The pump is autoclavable, which allows hygienic re-use



Technical innovation

The design of the pump is individually adapted to special customer requirements, which guarantees the minimum size for the application in question. For creating the pump chamber, a patent-registered piezo assembly process is used, minimizing the internal dead volume. This improves the back pressure capability for operating with gases and allows self-priming and bubble tolerance when handling incompressible media like water.

Special membrane valves with a combined hard/soft seal guarantee increased tightness against back flow.

State of development

Demonstrators

Various models of robust stainless steel micropumps have already been implemented by means of laser beam welded multi-layer joints.

Automation

For the novel piezo assembly process, adhesive dosing equipment with pick-and-place automation was used. This makes partly automated fabrication possible.


Fabrication

The micropumps have already been fabricated in batch sizes more than 100.

Technical data

	μ P303	μ P304
Size	Ø 29 mm x 2,6 mm	Ø 20 mm x 2,1 mm
Weight	13 g	5 g
Material	Stainless steel Silicon	Stainless steel Silicon
Max. flowrate (air)	200 ml/min	50 ml/min
Max. flowrate (fluid)	80 ml/min	16 ml/min
Back pressure capability (air)	20 kPa	25 kPa
Back pressure capability (fluid)	31 kPa	75 kPa
Energy consumption	< 400 mW	< 300 mW

Flow rate characteristics of the stainless steel micropumps in respect of their size:



3 Stainless steel micropumps
 μ P303 (Ø 20 mm) and μ P304 (Ø 29 mm)
 4 Diaphragm valve